



Radicon provides a global resource for delivering high integrity solutions backed by a wealth of technical experience across a broad range of industries. It encompasses geared motors, positioning and complete drive solutions, worm gear units and industrial reducers, designed to combine extraordinary flexibility, rugged reliability and advanced performance.

The combined technical expertise and manufacturing know-how of Benzlers and Radicon, ensures the highest possible standards of product design and performance, ensuring total customer satisfaction.

benzlers*
radicon*



Industrial Motors and Gears Limited

Tel. 01642 467999 Mob. 07815 889460 Fax. 01642 467988 Email. sales@imag-uk.com

www.imag-uk.com



Product Brochure







SERIES M IN LINE

HELICAL GEARED

MOTORS AND

REDUCERS









Key dimensions throughout the easy installation into existing

range are interchangeable with many manufacturers allowing applications.

Unit Sizes: 01, 02, 03, 04, 05, 06, 07, 08, 09, 10, 13, and 14 Up to 121 HP

Proven design geared motors

with dry connection between

motor and gearbox for easy

removal of the motor.

Up to 97,000 lb.ln 3.6/1 to 58/1 in two stage, upto

16200/1 in combined form Motor Sizes

ANGLE HELICAL BEVEL HELICAL REDUCERS

03, 04, 05, 06, 07, 08, 09, 10, and 12 Up to 60 HP Input Power Up to 121 HP **Output Torque:** Up to 109,000 lb.In Gear Ratios:

8.0/1 to 160/1 in three stage, up to 35000/1 in combined form

IEC Frames from 56C to 405TC IEC Frames from 56C to 405TC

ANGLE HELICAL WORM GEARED MOTORS AND

Available with Drywell System for maximum protection against oil contamination on vertical shaft mixing and aerating applications.

03, 04, 05, 06, 07, 08, 09, and 10 Up to 89,000 lb.In

8.0/1 to 250/1 in two stage, up to 60000/1 in combined form Motor Sizes: IEC Frames from 56C to 326TC

SHAFT MOUNT HELICAL GEARED MOTORS AND REDUCERS

SERIES F PARALLEL

Available with market leader KIBO tapered bushing system to allow trouble free removal of hollow shaft and gearboxes.

02, 03, 04, 05, 06, 07, 08, 09, 10, 11 and 12 Input Power Up to 148 HP Output Torque: Up to 146,000 lb.ln 5.0/1 to 100/1 in 2 stage, up to 5600/1 in combined form Hollow shaft: 1.0" to 4"

Unit Sizes:

Motor Sizes:

IEC Frames from 56C to 326TC

14, 15, 16, 17, 18, 19, 21, 22 Up to 2,012 HP Up to 1,433,000 lb.ln 6.3/1 to 315/1/1 in multistage, up to 70000/1 in combined form Up to 9.5" diameter Motor Sizes IEC Frames from 254TC to

405TC

UNITS





SERIES G HELICAL SERIES J HELICAL PARALLEL SHAFT AND SHAFT MOUNT SPEED BEVEL HELICAL RIGHT REDUCERS ANGLE DRIVE GEAR

Available with unique KIBO® Incorporating 3 stage high integrity sealing, split gear case tapered bushing system to allow design for easy maintenance. trouble free removal of hollow shaft gearboxes.

11/12, 21/22, 31/32, 51/52, 71/72, 40, 50, 63, 71 100, 110, 125, 140, 160, 190 Up to 829 HP **Output Torque** Up to 511,000 lb.ln Gear Ratios: 5:1 to 20:1 Hollow shaft: 1.4" to 7.5"

GEARED MOTORS AND REDUCERS

SERIES A

The Series A Mid Range and Heavy

Duty units can be mounted in

the worm under, worm over and

positions and provide a choice of

410, 510, 610, 730, 860, 1002,

1252, 1602, 2002, 10, 12, 14, 17,

from 5:1 to 70:1 single reduction

and 4900/1 in double reduction

outputshaft vertical mounting

shaft arrangements.

20,

format

Output Shaft:

Input Power

Up to 759 HP

Output Torque

Up to 425,000 lb.In

SERIES BS RIGHT

ANGLE WORM

Universal compact aluminium housing. Tufram® coated range with stainless steel hollow shaft available for food grade wash

Unit Sizes:

Up to 9 HP Output Torque: Up to 2750 lb.In 6.67/1 to 104/1 (without prestep) Hollow shaft: 0.75" to 1.5"











ROLOID GEAR PUMPS



SERIES X COUPLINGS

Supplied as individual products or engineered into complete linear motion packages, Suitable for numerous applications including linear motion, positioning, pressing and load adjustment.

27, 40, 58, 66, 86, 100, 125, 200 2 lb to 110 st up to 16'/min Stainless Steel

construction available

Suitable for pumping a wide variety of liquids which have a lubricating property, in applications such as Engines, Compressors, Gearboxes, Rolling Mills, Machine Tools, Process Plant, Pumping Sets and Turbines. HST version specifically designed for screw compressor applications.

Unit Sizes: 9, 7, 6, 5, 4, 3, 2.5, 2, 1.5 up to 600 USg/min

A comprehensive range of shaft couplings, incorporating, gear type, Cone Ring pin and bush type and Nylicon, allowing both parallel offset and angular misalignment, virtually maintenance free, offering excellent durability.

Unit Sizes: Accommodating shaft size up to 22" dia. Load Capacity: Up to 9,735,000 lb.In

* Not available Atex certified

THROUGH LIFE COSTS

Whether you use drive and linear motion systems in your plant production line, or are a machine builder wishing to offer your customer the most reliable machine possible, we recognise the importance of minimising through-life cost.

A combination of rugged reliability, providing maximum life span and userfriendly design, enabling easy maintenance, ensures that the products we offer are easy to live with, giving you peace of mind and allowing you to focus on the important areas of your day to day business.

CUSTOMISED & SYSTEM SOLUTIONS

We recognise that a standard off the shelf product is not always the best solution for our customers needs. The design principles which we incorporate into our product range enable a high degree of product flexibility, enabling many alternative solutions to be offered.

Our experienced sales and engineering teams are able to provide both complete drive and linear motion system packages as well as a full customisation service, providing a specific product modification to meet your exact needs.

Atex - All our products can be supplied Atex certified on normal lead times *

APPLICATION EXPERTISE AT YOUR SERVICE

An unrivalled depth of customer application expertise stretching back over 150 years enables us to provide the optimum solution for your drive requirements. Our team of Application Engineers are available to review your needs, understand your problems and recommend the best possible drive or linear system solution to maximise the operation of your equipment and minimise the through life cost.